

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client :	Proline Floor Unit 2	S		Test Numbe Issue Date	r : :	18-00271 6/06/2018				
		ain Cook Drive SW 2229		Print Date	:	6/06/2018				
Sample D	Description	Engineered ply floorboards End Use : Floating Floorboards Nominal Composition : Oa Nominal Mass per Unit Area/E	ik Plywood							
S/ISO 9239.1-2003		Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a Radiant Heat Source								
		Date of Sample Arrival 18/05/2018								
		Date Tested 05/06/2018								
		Date Tested		05/06/2018						
		Date Tested CHF Value	1		3	Mean				
			1 4.4		3	Mean	kW/m²			
		CHF Value		2		Mean - 3.4				
		CHF Value Length	4.4	2 - 3.1 3	-	-				
		CHF Value Length Width	4.4 3.6	2 - 3.1 3	.6	- 3.4				
		CHF Value Length Width Smoke Value	4.4 3.6 1	2 - 3.1 3 2 -	- 6 3	- 3.4	kW/m² %.min			
		CHF Value Length Width Smoke Value Length	4.4 3.6 1 8	2 - 3.1 3 2 -	- .6 3 -	- 3.4 Mean -	kW/m² %.min			
		CHF Value Length Width Smoke Value Length Width	4.4 3.6 1 8	2 - 3.1 3 2 -	- .6 3 -	- 3.4 Mean - 17	kW/m² %.min			

Α

(C)





Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client :	Proline Floors	Test Number	:	18-002713
	Unit 2	Issue Date	:	6/06/2018
	33 - 35 Captain Cook Drive	Print Date	:	6/06/2018
	Caringbah NSW 2229			

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was clamped to a substrate of 6mm thick fibre reinforced cement board prior to testing.

131459

27824

C Australian Wool testing Authority Ltd Copyright - All Rights Reserved



the Managing Director of AWTA Ltd.

Accredited for compliance with ISO/IEC 17025 - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

: Accreditation No. : Accreditation No. : Accreditation No.

o. 983 o. 985 o. 1356



Page 2 of 2



0204/11/06

APPROVED SIGNATORY

SADY