Sorrento

GENERS coastal 5mm Vinyl Plank

Proline Floors Product Launch Presentation

What does Proline Stand For



• Professional Flooring company that exceeds customer and retailer expectations

• Our aim is to produce quality products that achieve minimal issues that adhere to the Proline standard



What are we releasing



• Market leading Vinyl Plank



Genero Coastal 5mm Vinyl Plank



SPECIFICATIONS

- Vinyl Plank
- ✓ 5mm Thickness
- ✓ 1524mm L x 228.6mm W
- ✓ 0.5mm wear layer
- P3 slip resistant

DESIGN

- ✓ 8 Colours
- Modern Technology
- One of the lowest expansion rates in the industry
- One of the highest dimensional stability in the industry

Genero Coastal 5mm Vinyl Plank




| Lifetime Residential Warranty | | Wear Layer 0.5mm | | P3 Slip Rating | Vinyl Plank | Super Stability | |
|--|------------------|-------------------------|----------|--------------------------|--|---------------------------|------------|
| Easy to Cut | Made Kore | | Thicknes | | 10 years Commercial warranty | | + |
| Format | Size | | | Surface emboss | | Quantity per box | M² per box |
| Plank | 1524mm x 228.6mm | | | | Polyurethane | 6 | 2.09 |

How do we achieve the Lowest Expansion Rate



- Results achieved by using new improved sheet fiberglass made with proprietary techniques
 - > Like a string, once it expands to the maximum length, it cannot expand anymore.
 - The fiberglass is sandwiched between the multiple layers of propriety PVC. The fiberglass binds to the PVC, preventing the PVC from expanding.



Independent 🐼 MAPA Expansion Ageing Test



- ✓ Planks where sent to Mapei for independent testing.
- ✓ Dimensional stability testing was conducted in accordance with EN1903 'Test method for adhesives for plastic or rubber floor coverings or wall coverings: Determination of dimensional changes after accelerated ageing'. The plank was heated to 80 degrees for 6 hours. The change in length and width are recorded. Then plank is then allowed to cool down and re measured after 24 hours.
- ✓ Mapei allows a maximum dimensional change of 0.2% when assessing adhesive suitability.

| | Initial reading | 6 hours to 80 degrees | 24 hours to 23 degrees | Mapei's test % limit | Mapei pass / fail |
|--------|--------------------|--------------------------|---------------------------|-------------------------|----------------------|
| Length | 0% | 0.02% | 0% | 0.2% | pass |
| Width | 0% | 0.14% | 0.03% | 0.2% | pass |

Recommended 🐼 MAPE/ Glues

The adhesives listed below are deemed suitable when used in accordance with their technical datasheets:

- Ultrabond Eco V4 Evolution: The latest technology hard set universal adhesive that offers higher grab and longer open time than Ultrabond Eco V4 SP. It can be used in applications where the LVP may reach 50°C.
- Ultrabond Eco V4 SP: A hard set adhesive that offers good initial grab and extended open times. It can be used in applications where the LVP may reach 50°C.
- Ultrabond Eco VS90 Plus: A traditional wet lay adhesive. It can be used in applications where the LVP may reach 50°C.
- Ultrabond Eco MS 4 LVT Wall: Single component silvlated adhesive. It is a 100% solids (no solvent nor water) and chemically cures to give excellent performance in internal, wet/damp areas, over non-absorbent substrates, and provides the highest temperature resistance.

Environmental factors (e.g. water exposure, service conditions) must always be taken into account when selecting a suitable adhesive for a specific application and the adhesive must always be used in accordance with its technical data sheet. Please contact a Mapei representative if you would like further information.

8 Amazing Designs





Australian Hardwood Designs





Bowral Spotted Gum Arrawarra Blackbutt


European Oak Designs





Genero Coastal Custom made Stair Nosings





Matching Stair Nosings Stair cases and step downs

Product Summary







0.5 mm WEAR LAYER

WATER

STAIN RESISTANT



HEAT RESISTANT

MATT

FINISH



00

DURABLE

REALISTIC WOODGRAIN





PET FRIENDLY

ACOUSTIC SOUND ABSORPTION

E

ECO FRIENDLY

SUPER

Benefits

One of the lowest expansion rates in the industry

One of the highest dimensional stability in the industry

Pricing



Job Price

- ▶ \$39.00 sqm
- Pallet Price
 - ▶ \$37.50 sqm
- Box Quantity
 - > 6 planks per box
- Sqm per Box
 - > 2.09 sqm per box
- Sqm per Pallet
 - > 131.67 sqm per pallet

